

Smuxi - Feature # 551: Set PATH before starting Smuxi on Windows

Status:	Closed	Priority:	Normal
Author:	Mirco Bauer	Category:	Frontend GNOME
Created:	11/29/2010	Assigned to:	Mirco Bauer
Updated:	11/06/2011	Due date:	
Complexity:			
Subject:	Set PATH before starting Smuxi on Windows		
Description:	From time to time Smuxi users report issues starting Smuxi on Windows after installation. If the user has a GTK+ besides the GTK# install in the PATH then Smuxi will fail to start as GTK# will try to load the libraries from the GTK+ install and fails. As Smuxi knows where GTK# is installed (as it checks the registry for it) it can create a start script which sets PATH automatically to the right location.		

Associated revisions

11/06/2011 05:36 PM - Mirco Bauer

[Frontend-GNOME] Prepend GTK# to PATH on Windows (closes: #551)

GTK# on Windows relies to load the GTK+ libraries from the right location via the PATH which it extends during the install. This works just fine as long as PATH is not including any other GTK+ library paths. For this reason we simply prepend the GTK#'s library path to the PATH environment variable when running on Windows.

History

10/16/2011 12:44 PM - Mirco Bauer

- Assigned to deleted (Mirco Bauer)

11/06/2011 05:39 PM - Mirco Bauer

- Category changed from Windows Installer to Frontend GNOME

- Assigned to set to Mirco Bauer

11/06/2011 05:47 PM - Mirco Bauer

- Status changed from New to Closed

- % Done changed from 0 to 100

Applied in changeset commit:"1ea976803f8e5f98f9229a674604bfb9883e4cc4".