

## Smuxi - Feature # 647: Shutdown sequence for persistent message buffers

<b>Status:</b>	Closed	<b>Priority:</b>	Normal
<b>Author:</b>	Mirco Bauer	<b>Category:</b>	Engine
<b>Created:</b>	11/16/2011	<b>Assigned to:</b>	Mirco Bauer
<b>Updated:</b>	12/20/2011	<b>Due date:</b>	
<b>Complexity:</b>	Medium		
<b>Subject:</b>	Shutdown sequence for persistent message buffers		
<b>Description:</b>	Persistent message buffers like Db4oMessageBuffer need to be properly Dispose()d so the data is flushed to the disk. Without this a smuxi-server restart (SIGTERM) or a smuxi-frontend-gnome quit will cause a loss of up to 15 messages (auto-flush happens on every 16th message).		

### Associated revisions

---

**12/20/2011 01:50 PM - Mirco Bauer**

[Engine] Implemented /shutdown command (closes: #647)

### History

---

**11/16/2011 07:26 AM - Mirco Bauer**

Alternative would be an timeout based flush, see #648

**12/20/2011 01:50 PM - Mirco Bauer**

- Target version set to 0.8.9

**12/20/2011 05:17 PM - Mirco Bauer**

- Status changed from New to Closed

- % Done changed from 0 to 100

Applied in changeset commit:"52d3df60105708ac8549085a83f53dc562c5d8d8".