Smuxi - Bug # 889: Endless loop when connecting to Hipchat

Status:	Closed	**Priority:**	Urgent
Author:	Mirco Bauer	**Category:**	Engine XMPP (Jabber)
Created:	10/17/2013	**Assigned to:**	Oliver Schneider
Updated:	12/20/2013	**Due date:**	
Complexity:			
Found in Version:	master/bf61473		
Subject:	Endless loop when connecting to Hipchat		

Description:

<pre>
18:22:59 READ:
<iq xmlns="jabber:client" to="53950_369105@chat.hipchat.com/smuxi" type="error" id="agsXMPP_44">
 <bind xmlns="urn:ietf:params:xml:ns:xmpp-bind">
  <jid>53950_369105@chat.hipchat.com/smuxi</jid>
 </bind>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
 </error>
 <error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
```
```

```
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
```

```
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
```

```
  <error code="501" type="cancel">
   <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
   <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
   <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
   <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
   <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
 </iq>

 </pre>
```

Associated revisions

10/18/2013 04:04 PM - Oliver Schneider

[lib/agsxmpp] prevent service-unavailable iq loop with the server (closes: #889)

History

10/18/2013 01:03 PM - Andrés G. Aragoneses

- File out.txt added

Attaching log file of what gets outputted in the terminal (when using "make run") when connecting to hipchat and getting the loop.

10/18/2013 01:20 PM - Andrés G. Aragoneses

new log:

```
<pre>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
</iq>
13:19     WRITE:
<iq id="agsXMPP_4" type="error" from="13856_351305@chat.hipchat.com/smuxi">
  <bind xmlns="urn:ietf:params:xml:ns:xmpp-bind">
    <jid>13856_351305@chat.hipchat.com/smuxi</jid>
  </bind>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
```

<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />

```
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
</iq>
13:19     READ:
<iq xmlns="jabber:client" to="13856_351305@chat.hipchat.com/smuxi" type="error" from="chat.hipchat.com" id="agsXMPP_5">
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
    <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error code="501" type="cancel">
    <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
  </error>
  <error type="cancel">
```

<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
</iq>
13:19 WRITE:
<iq id="agsXMPP_5" type="error" from="13856_351305@chat.hipchat.com/smuxi" to="chat.hipchat.com">
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>

<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
</iq>
13:19 READ:
<iq xmlns="jabber:client" to="13856_351305@chat.hipchat.com/smuxi" type="error" from="chat.hipchat.com" id="agsXMPP_5">
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />

</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
</iq>
13:19 WRITE:
<iq id="agsXMPP_5" type="error" from="13856_351305@chat.hipchat.com/smuxi" to="chat.hipchat.com">
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">

```
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
```

<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
</iq>
13:19 READ:
<iq xmlns="jabber:client" to="13856_351305@chat.hipchat.com/smuxi" type="error" id="agsXMPP_4">
<bind xmlns="urn:ietf:params:xml:ns:xmpp-bind">
<jid>13856_351305@chat.hipchat.com/smuxi</jid>
</bind>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />

</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
</iq>
13:19 WRITE:
<iq id="agsXMPP_4" type="error" from="13856_351305@chat.hipchat.com/smuxi">
<bind xmlns="urn:ietf:params:xml:ns:xmpp-bind">
<jid>13856_351305@chat.hipchat.com/smuxi</jid>
</bind>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
<feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
<service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">

```
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error code="501" type="cancel">
  <feature-not-implemented xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
<error type="cancel">
  <service-unavailable xmlns="urn:ietf:params:xml:ns:xmpp-stanzas" />
</error>
```

</iq>
</pre>

10/20/2013 12:37 PM - Oliver Schneider

- Status changed from New to Closed

- % Done changed from 0 to 100

Applied in changeset commit:"05c3ece2f373baa59f6d080368b6526ee4003622".

12/20/2013 05:27 AM - Mirco Bauer

- Target version changed from 26 to 0.10

Files

out.txt	138.8 KB	10/18/2013	Andrés G. Aragoneses